

Fiber optic products

Fiber optic adaptors are used to calibrate two fiber optic connectors. OPCSUN could offer SM, MM, APC; SIMPLEX, DUPLEX adapter etc.

MATERIAL

	MTRJ/SM	MTRJ /MM
External Housing	Plastic--Black	Plastic--Black

SC type MTRJ adapter is available up on request.



SPECIFICATIONS

	MTRJ /SM	MTRJ /MM
Insertion Loss	<0.20dB	<0.20dB
Tensile Strength Of Welding (Plastic Adapter Only)	> 100 N	
Withdraw Force(g/f)	200-600	
Durability	<0.20 dB typical change, 1000 matings	
Operating Temperature [°C]	-25~+70	
Storage Temperature [°C]	-40~+85	

FEATURES

- ✚ Compliant With **ANSI, TIA/EIA and JIS** etc
- ✚ Meets UI94-V0o Flammability Requirements
- ✚ High Precision Alignment
- ✚ Low Insertion Loss and Back Reflection Loss
- ✚ Excellent Interchangeability
- ✚ Excellent Repeatability
- ✚ Good Temperature Characteristic
- ✚ Choice of Housing Material and Sleeve Material

APPLICATIONS

- ✚ Telecom, Access Network
- ✚ Optical Fiber CATV
- ✚ Terminal of The Devices and Multimedia
- ✚ Testing And Medical Devices
- ✚ Optical Fiber LAN and Access Network
- ✚ Industry and Military Applications

