


Fiber optic products

Fiber optic adapters are used to calibrate two fiber optic connectors. OPCSUN could offer SM, MM, APC; SIMPLEX, DUPLEX adapter etc.

MATERIAL

	D4/SM	D4/MM
External Housing	Metal	
Sleeve	Zirconia Ceramic	Phosphor Bronze



SPECIFICATIONS



	D4/SM	D4/MM
Insertion Loss	<0.20db	<0.20db
Tensile Strength Of Welding (Plastic Adapter Only)	> 100 N	
WITHDRAW FORCE(G/F)	200-600	
Durability	<0.20 Db Typical Change, 1000 Matings	
Operating Temperature [°C]	-25~+70	
Storage Temperature [°C]	-40~+85	

FEATURES

- ✦ Compliant With **ANSI, TIA/EIA and JIS** Etc
- ✦ Meets UI94-V0 Flammability Requirements
- ✦ High Precision Alignment
- ✦ Low Insertion Loss and Back Reflection Loss
- ✦ Excellent Interchangeability
- ✦ Excellent Repeatability
- ✦ Good Temperature Characteristic
- ✦ Choice of Housing Material and Sleeve Material

APPLICATIONS

- ✦ Telecom, Access Network
- ✦ Optical Fiber CATV
- ✦ Terminal of The Devices and Multimedia
- ✦ Testing and Medical Devices
- ✦ Optical Fiber LAN and Access Network
- ✦ Industry and Military Applications

